



复旦微电子

FM11NT020

***NFC Forum Type2 Tag compliant IC with
232 bytes user memory and field detection***

Datasheet

Apr.2014



INFORMATION IN THIS DOCUMENT IS INTENDED AS A REFERENCE TO ASSIST OUR CUSTOMERS IN THE SELECTION OF SHANGHAI FUDAN MICROELECTRONICS GROUP CO., LTD PRODUCT BEST SUITED TO THE CUSTOMER'S APPLICATION; THEY DO NOT CONVEY ANY LICENSE UNDER ANY INTELLECTUAL PROPERTY RIGHTS, OR ANY OTHER RIGHTS, BELONGING TO SHANGHAI FUDAN MICROELECTRONICS GROUP CO., LTD OR A THIRD PARTY.

WHEN USING THE INFORMATION CONTAINED IN THIS DOCUMENTS, PLEASE BE SURE TO EVALUATE ALL INFORMATION AS A TOTAL SYSTEM BEFORE MAKING A FINAL DECISION ON THE APPLICABILITY OF THE INFORMATION AND PRODUCTS.

PURCHASERS ARE SOLELY RESPONSIBLE FOR THE CHOICE, SELECTION AND USE OF THE SHANGHAI FUDAN MICROELECTRONICS GROUP CO., LTD PRODUCTS AND SERVICES DESCRIBED HEREIN, AND SHANGHAI FUDAN MICROELECTRONICS GROUP CO., LTD ASSUMES NO LIABILITY WHATSOEVER RELATING TO THE CHOICE, SELECTION OR USE OF THE SHANGHAI FUDAN MICROELECTRONICS GROUP CO., LTD PRODUCTS AND SERVICES DESCRIBED HEREIN. UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED SHANGHAI FUDAN MICROELECTRONICS GROUP CO., LTD REPRESENTATIVE, SHANGHAI FUDAN MICROELECTRONICS GROUP CO., LTD PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE.

FUTURE ROUTINE REVISIONS WILL OCCUR WHEN APPROPRIATE, WITHOUT NOTICE. CONTACT SHANGHAI FUDAN MICROELECTRONICS GROUP CO., LTD SALES OFFICE TO OBTAIN THE LATEST SPECIFICATIONS AND BEFORE PLACING YOUR PRODUCT ORDER. PLEASE ALSO PAY ATTENTION TO INFORMATION PUBLISHED BY SHANGHAI FUDAN MICROELECTRONICS GROUP CO., LTD BY VARIOUS MEANS, INCLUDING SHANGHAI FUDAN MICROELECTRONICS GROUP CO., LTD HOME PAGE ([HTTP://WWW.FMSH.COM/](http://WWW.FMSH.COM/)).

PLEASE CONTACT SHANGHAI FUDAN MICROELECTRONICS GROUP CO., LTD LOCAL SALES OFFICE FOR THE SPECIFICATION REGARDING THE INFORMATION IN THIS DOCUMENT OR SHANGHAI FUDAN MICROELECTRONICS GROUP CO., LTD PRODUCTS.

Trademarks

Shanghai Fudan Microelectronics Group Co., Ltd name and logo, the “复旦” logo are trademarks or registered trademarks of Shanghai Fudan Microelectronics Group Co., Ltd or its subsidiaries in China.

Shanghai Fudan Microelectronics Group Co., Ltd, Printed in the China, All Rights Reserved.



Contents

CONTENTS	3
1 PRODUCT OVERVIEW.....	4
1.1 INTRODUCTION.....	4
1.2 FEATURES.....	4
1.2.1 RF Interface.....	4
1.2.2 EEPROM.....	4
1.2.3 NFC Forum Tag 2 Type compliance	4
1.2.4 Field detection	4
1.2.5 Security	5
1.2.6 Cascaded UID.....	5
1.2.7 Anticollision	5
1.3 BLOCK DIAGRAM.....	5
1.4 PINNING INFORMATION.....	6
2 ORDERING INFORMATION	8
3 PACKAGE OUTLINE.....	9
3.1 DFN4	9
3.2 TSOT	10
REVISION HISTORY.....	11
SALES AND SERVICE	12



1 Product Overview

1.1 Introduction

FM11NT020 is primarily designed for NFC Forum Type 2 Tag applications in electronics (i.e. connection handover, Bluetooth simple pairing, Wi-Fi Protected set-up, device authentication, gaming and others). Please consult Fudan Micro Electronics Company for more documents.

1.2 Features

1.2.1 RF Interface

- ISO/IEC 14443A
- Contactless transmission of data and supply energy (no battery needed)
- Operating distance: up to 100 mm (depending on various parameters as e.g. field strength and antenna geometry)
- Operating frequency: 13.56 MHz
- Fast data transfer: 106 Kbit/s
- High data integrity: 16-bit CRC, parity, bit coding, bit counting
- True anticollision
- 7 byte serial number (cascade level 2 according to ISO/IEC 14443-3)

1.2.2 EEPROM

- 252 bytes of total memory, divided in 63 pages (4 bytes each)
- 232 bytes of user r/w memory area, divided in 58 pages (4 bytes each)
- Field programmable read-only locking function per page of the first 16 pages and per 2 pages of rest of the memory
- 32-bit user definable One-Time Programmable (OTP) area
- Data retention of 10 years
- Write endurance 100000 cycles

1.2.3 NFC Forum Tag 2 Type compliance

FM11NT020 IC provides full compliance to the NFC Forum Tag 2 Type technical specification and enables NDEF data structure configurations .

1.2.4 Field detection

FM11NT020 features an additional RF field detection functionality. The corresponding output signal can be used as interrupt source to e.g. wake up an embedded microcontroller or trigger further actions. Typical applications are Bluetooth and Wi-Fi pairing.

1.2.5 Security

- Anti-cloning support by unique 7-byte serial number for each device, UID is unchangeable.
- Field programmable read-only locking function per page of the first 16 pages and per 2 pages of rest of the memory.

1.2.6 Cascaded UID

The anticollision function is based on an IC individual serial number called Unique IDentifier. The UID of the FM11NT020 is 7 bytes long and supports cascade level 2 according to ISO/IEC 14443-3.

1.2.7 Anticollision

An intelligent anticollision function according to ISO/IEC 14443 allows to operate more than one card in the field simultaneously. The anticollision algorithm selects each card individually and ensures that the execution of a transaction with a selected card is performed correctly without data corruption resulting from other cards in the field.

1.3 Block diagram




Fig 1-1 FM11NT020 Block diagram

1.4 Pinning information




Fig 1-2 Pin configuration for DFNWB1.2X1.6-4L

Pin number	Symbol	Description
1	GND	GND connection
2	IN1	Antenna connection IN1
3	IN2	Antenna connection IN2
4	FD	RF Field Detect connection

Table 1-1 Pin description of the DFNWB1.2X1.6-4L package




Fig 1-3 Pin configuration for TSOT23-5L



Pin number	Symbol	Description
1	GND	GND connection
2		Dump pin
3	IN2	Antenna connection IN2
4	IN1	Antenna connection IN1
5	FD	RF Field Detect connection

Table 1-2 Pin description of the TSOT23-5L

2 Ordering information

Type Number	Package Name	Packing
FM11NT020-DNB-T-G	DFN4	Tape and Reel
FM11NT020-ST-T-G	TSOT23-5	Tape and Reel

FM 11NT 02 0 -XXX -C -H

Company Name

FM=Shanghai Fudan Microelectronics Group Company Limited

Product Family Name

11NT=NFC TAG Product

Memory

02= about 2K bit EEPROM

Generation number

0=The first generation

Package

DNB= DFNWB1.2x1.6-4L

ST=TSOT23-5L

Packing

T= Tape and Reel

U= Tube

HSF code

G=ROHS Compliant, Halogen-free, Antimony-free

3 Package outline

3.1 DFN4




Fig 3-1 Package outline DFN4

3.2 TSOT




Fig 3-1 Package outline TSOT23-5L

Revision history

Version	Publication date	Pages	Paragraph or Illustration	Revise Description
1.0	Apr.2014	12		Initial release



Sales and Service

Shanghai Fudan Microelectronics Group Co., Ltd.

Address: Bldg No. 4, 127 Guotai Rd,
Shanghai City China.
Postcode: 200433
Tel: (86-021) 6565 5050
Fax: (86-021) 6565 9115

Shanghai Fudan Microelectronics (HK) Co., Ltd.

Address: Unit 506, 5/F., East Ocean Centre, 98 Granville Road, Tsimshatsui East, Kowloon, Hong Kong
Tel: (852) 2116 3288 2116 3338
Fax: (852) 2116 0882

Beijing Office

Address: Room 423, Bldg B, Gehua Building,
1 QingLong Hutong, Dongzhimen Alley north Street,
Dongcheng District, Beijing City, China.
Postcode: 100007
Tel: (86-010) 8418 6608
Fax: (86-010) 8418 6211

Shenzhen Office

Address: Room.1301, Century Bldg, No. 4002, Shengtingyuan Hotel, Huaqiang Rd (North),
Shenzhen City, China.
Postcode: 518028
Tel: (86-0755) 8335 0911 8335 1011 8335 2011 8335 0611
Fax: (86-0755) 8335 9011

Shanghai Fudan Microelectronics (HK) Ltd Taiwan Representative Office

Address: Unit 1225, 12F., No 252, Sec.1 Neihu Rd., Neihu Dist., Taipei City 114, Taiwan
Tel : (886-2) 7721 1889
Fax: (886-2) 7722 3888

Shanghai Fudan Microelectronics (HK) Ltd Singapore Representative Office

Address : 237, Alexandra Road, #07-01 The Alexcier, Singapore 159929
Tel : (65) 6472 3688
Fax: (65) 6472 3669

Shanghai Fudan Microelectronics Group Co., Ltd NA Office

Address :2490 W. Ray Road Suite#2
Chandler, AZ 85224 USA
Tel : (480) 857-6500 ext 18

Web Site: <http://www.fmsh.com/>